

## 1000°F / 537°C: DeltaGlass™ Fiberglass Knitted Tape

Very High Temperature & Heat Resistant

Plain Tape & Bolt Hole / Ladder Tape: *Premium Grade*



These knitted tapes are fabricated from high quality type E fiberglass that will not burn and will withstand continuous exposure to temperatures of 1000°F / 537°C.

This material resists most acids and alkalis and is unaffected by most bleaches and solvents. It is highly flexible and conformable.

The base fiber is manufactured to the specifications of ASTM D-578, ASTM committee D13, and subcommittee D13.18.

Knitted tapes are extremely flexible and conformable, more so than the same dimension tape in a woven style.

1000°F / 537°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature & Heat Resistant Fiberglass Knitted Tape: Plain & Bolt Hole - <i>Premium</i>				
1/8" / 3mm Thick Knitted Plain Tape				
Width inch / mm / dash #			Part Number	Price per Roll
1"	25	-16	T-FG-K-M025-16	\$ 71.67
1 1/4"	32	-20	T-FG-K-M032-20	\$ 90.00
1 1/2"	38	-24	T-FG-K-M038-24	\$ 110.00
1 3/4"	44	-28	T-FG-K-M044-28	\$ 135.00
2"	51	-32	T-FG-K-M051-32	\$ 156.67
2 1/2"	64	-40	T-FG-K-M064-40	\$ 180.00
3"	76	-48	T-FG-K-M076-48	\$ 210.00
4"	102	-64	T-FG-K-M102-64	\$ 256.67
5"	127	-80	T-FG-K-M127-80	\$ 306.67
1/8" / 3mm Thick Knitted Bolt Hole / Ladder Tape				
Width inch / mm / dash #			Part Number	Price per Roll
1"	25	-16	T-FG-K-BH-M025-16	\$ 61.67
1 1/4"	32	-20	T-FG-K-BH-M032-20	\$ 78.33
1 1/2"	38	-24	T-FG-K-BH-M038-24	\$ 90.00
1 3/4"	44	-28	T-FG-K-BH-M044-28	\$ 100.00
2"	51	-32	T-FG-K-BH-M051-32	\$ 110.00
2 1/2"	64	-40	T-FG-K-BH-M064-40	\$ 133.33
3"	76	-48	T-FG-K-BH-M076-48	\$ 163.33
4"	102	-64	T-FG-K-BH-M102-64	\$ 210.00
5"	127	-80	T-FG-K-BH-M127-80	\$ 260.00

Each roll contains 100 feet / 30 metres.

**This Product is NOT Available By-The-Foot – Full Rolls Only**

To aid in mounting this tape onto surfaces, FlangeStik™ pressure sensitive adhesive spray can be used to place the tape in situ temporarily. Permanent fasteners or grab strips should be installed prior to heating of the area sprayed above 200°F. The adhesive will “smoke-off” at elevated temperatures.