

392°F / 200°C: Fiberglass Fine Weave Tape with Silicone Adhesive
Glass Cloth High Temperature & Heat Resistant High Adhesion Tape



- FlameShield™ 19166 glass cloth tape is a high temperature fine weave fiberglass tape with a very high adhesion silicone adhesive.
- 3000 volt dielectric strength.
- .007" thick.
- UL recognized and meets Mil-i-19166C.
- Adhesion of 40oz/in.
- Tensile strength 180 lbs/in.
- Insulation class "H".
- This tape is widely used for electrical installations and repairs. Used on splices requiring high abrasion resistance and mechanical strength. Widely used in marine and aviation applications.

FlameShield™ High Temperature Fiberglass Tape with Silicone Adhesive UL Recognized & Meets Mil-I-19166			
Part Number	Tape Width inch / mm		Price per Roll
T-FG-SA-19166-M013-08	0.5	13	\$ 35.84
T-FG-SA-19166-M025-16	1.0	25	\$ 66.25
T-FG-SA-19166-M038-24	1.5	38	\$ 130.33
T-FG-SA-19166-M051-32	2.0	51	\$ 173.77

0.5" and 1" wide tapes are normally stock; 1.5" and 2" wide are custom slit from a log and usually takes 2 to 3 days to process through our cutting room.

Standard length is 66 Feet / 20 Metres, rolled