

## Very High Temperature Fiberglass Braided Sleeve: Premium Grade



This Braided fiberglass sleeve is fabricated from high quality type E fiberglass that will not burn and will withstand continuous exposure to temperatures of 1000°F / 537°C.

This material resists most acids and alkalis and is unaffected by most bleaches and solvents. It is highly flexible and conformable.

The base fiber is manufactured to the specifications of ASTM D-578, ASTM committee D13, and subcommittee D13.18.

1000°F / 537°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature Fiberglass Braided Sleeve - Premium Grade				
ID Size inch / mm / dash#			Part Number	Price per Foot
1/2"	13	-08	AB-BFSP-M013-08	\$ 2.17
5/8"	16	-10	AB-BFSP-M016-10	\$ 2.17
3/4"	19	-12	AB-BFSP-M019-12	\$ 3.00
7/8"	22	-14	AB-BFSP-M022-14	\$ 3.00
1"	25	-16	AB-BFSP-M025-16	\$ 3.67
1 1/4"	32	-20	AB-BFSP-M032-20	\$ 4.33
1 3/8"	35	-22	AB-BFSP-M035-22	\$ 4.33
1 1/2"	38	-24	AB-BFSP-M038-24	\$ 4.33
1 3/4"	44	-28	AB-BFSP-M044-28	\$ 6.33
1 7/8"	48	-30	AB-BFSP-M048-30	\$ 6.33
2"	51	-32	AB-BFSP-M051-32	\$ 6.33
2 1/4"	57	-36	AB-BFSP-M057-36	\$ 8.67
2 1/2"	64	-40	AB-BFSP-M064-40	\$ 8.67
2 3/4"	70	-44	AB-BFSP-M070-44	\$ 8.67
3"	76	-48	AB-BFSP-M076-48	\$ 10.50
3 1/4"	83	-52	AB-BFSP-M083-52	\$ 10.50
3 1/2"	89	-56	AB-BFSP-M089-56	\$ 12.83
3 3/4"	95	-60	AB-BFSP-M095-60	\$ 12.83
4"	102	-64	AB-BFSP-M102-64	\$ 12.83

Knitted or Braided Fiberglass Sleeveing is typically used to protect hoses, cables and wires from high temperatures up to 1000°F / 537°C continuous use. Extremely flexible and conformable.

**This Product is Available By-The-Foot**