

Very High Temperature Fiberglass Braided Sleeve: Industrial Grade



- Braided Industrial sleeve
- Available in Thin Wall (1/16") and Thick Wall (1/8").

This braided sleeve is fabricated from high quality type E fiberglass that will not burn and will withstand continuous exposure to temperatures of 1000°F / 537°C.

This material resists most acids and alkalis and is unaffected by most bleaches and solvents. It is highly flexible and conformable. The base fiber is manufactured to the specifications of ASTM D-578, ASTM committee D13, and subcommittee D13.18.

1000°F / 537°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature Fiberglass Braided Sleeve Industrial Grade							
Part Number	Size inch / mm / -dash			Thin Wall Feet per spool / Price per foot		Thick Wall Feet per spool / Price per foot	
	AB-BFS-M006-04-X	.250	6	-4	1400	0.56	700
AB-BFS-M010-06-X	.375	10	-6	1400	0.76	600	1.20
AB-BFS-M013-08-X	.500	13	-8	1000	0.92	330	2.00
AB-BFS-M016-10-X	.625	16	-10	900	0.96	315	2.16
AB-BFS-M019-12-X	.750	19	-12	750	1.01	300	2.18
AB-BFS-M022-14-X	.875	22	-14	650	1.12	300	2.20
AB-BFS-M025-16-X	1.000	25	-16	500	1.52	290	2.40
AB-BFS-M032-20-X	1.250	32	-20	450	1.80	280	2.60
AB-BFS-M038-24-X	1.500	38	-24	350	2.36	225	3.04
AB-BFS-M044-28-X	1.750	44	-28	300	2.52	208	3.24
AB-BFS-M051-32-X	2.000	51	-32	250	2.64	190	4.36
AB-BFS-M064-40-X	2.500	64	-40	225	2.96	180	4.76
AB-BFS-M076-48-X	3.000	76	-48	200	3.20	175	5.92
AB-BFS-M089-56-X	3.500	89	-56	190	3.56	170	6.40
AB-BFS-M102-64-X	4.000	102	-64	175	5.88	140-	7.20
AB-BFS-M127-80-X	5.000	127	-80	120	6.16	100	12.28

For the "X" value in the part number:
use "1" to specify Thin Wall; use "2" to specify Thick Wall

Thin Wall = 1/16" / 1.59mm • Thick Wall = 1/8" / 3.18mm

This Product is Available By-The-Foot