

Very High Temperature Heat Resistant Vermiculite Coated Fiberglass Tape: Premium Grade



Vermiculite coated fibreglass tape is manufactured from texturized fiberglass yarns then coated with Vermiculite, a 100% inorganic dispersion. Vermiculite coated tape will withstand temperatures up to 1500°F / 815°C constant exposure with excursions to 2000°F / 1093°F. Also offers additional abrasion resistance and stiffness.

Offered in *Plain* and *Drop Warp*. Drop Warp tape has lengthwise yarns missing from the center of the tape to allow fasteners to pass through the tape for

assembly onto access doors, etc. This is also called a Ladder Tape or Bolt-hole tape.

Premium grade tape has a higher bulk than Industrial grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fiberglass content). Available with and without Pressure Sensitive Adhesive (PSA).

1500°F / 815°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature Heat Resistant Vermiculite Coated Fiberglass Tape Premium Grade					
Part Number	Width in / mm		Price per Roll By Thickness: A / B / C		
			"A" no PSA / with PSA	"B" no PSA / with PSA	"C" no PSA / with PSA
AB-VTP-M013-08-X-Z**	.5	13	\$ 79.50 / \$ 122.47	\$ 93.33 / \$ 136.30	NA
AB-VTP-M019-12-X-Z**	.75	19	\$ 81.20 / \$ 123.97	\$ 96.67 / \$ 141.50	\$ 153.30 / \$ 201.47
AB-VTP-M025-16-X-Z	1.0	25	\$ 82.93 / \$ 133.23	\$ 99.83 / \$ 150.80	\$ 206.50 / \$ 256.13
AB-VTP-M032-20-X-Z	1.25	32	\$ 85.57 / \$ 144.87	\$ 111.27 / \$ 170.57	\$ 231.57 / \$ 290.87
AB-VTP-M038-24-X-Z	1.5	38	\$ 87.50 / \$ 147.62	\$ 114.58 / \$ 178.65	\$ 268.83 / \$ 322.17
AB-VTP-M051-32-X-Z	2.0	51	\$ 93.67 / \$ 160.47	\$ 128.90 / \$ 195.37	\$ 288.07 / \$ 354.87
AB-VTP-M064-40-X-Z	2.5	64	\$ 100.67 / \$ 175.66	\$ 144.31 / \$ 219.32	\$ 323.03 / \$ 398.03
AB-VTP-M076-48-X-Z	3.0	76	\$ 111.93 / \$ 193.17	\$ 167.03 / \$ 446.67	\$ 366.33 / \$ 467.96
AB-VTP-M089-56-X-Z	3.5	89	\$ 123.03 / \$ 206.33	\$ 182.11 / \$ 265.40	\$ 398.78 / \$ 497.58
AB-VTP-M102-64-X-Z	4.0	102	\$ 135.40 / \$ 248.60	\$ 198.20 / \$ 292.56	\$ 443.17 / \$ 516.33
AB-VTP-M127-80-X-Z	5.0	127	\$ 157.57 / \$ 278.20	\$ 262.73 / \$ 374.67	\$ 545.66 / \$ 657.53
AB-VTP-M152-96-X-Z	6.0	152	\$ 162.97 / \$ 294.30	\$ 286.43 / \$ 384.40	\$ 600.50 / \$ 698.51

- For the "X" value, specify A, B or C in part number to correspond to the desired thickness
A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm C = 1/4" / .250" / 6.35mm
- For "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape.
- Add "-PSA" to the part number for tape with PSA coating.

Example: AB-VTP-B-24-P-PSA is a .125" thick tape, 1.5" wide, Plain style, with PSA coating

- All tapes are 100 foot lengths.
- ** -08 / .5" / 13mm and -12 / .75" / 19mm width tapes are not available in Drop Warp

Very High Temperature Heat Resistant Vermiculite Coated FiberglassTape: *Industrial Grade*



Vermiculite coated fiberglass tape is manufactured from texturized fiberglass yarns then coated with Vermiculite, a 100% inorganic dispersion. Vermiculite coated tape will withstand temperatures up to 1500°F / 815°C constant exposure with excursions to 2000°F / 1093°F. Also offers abrasion resistant stability.

Offered in *Plain* and *Drop Warp*. Drop Warp tape has lengthwise yarns missing from the center of the

tape to allow fasteners to pass through the tape for assembly onto access doors, etc. This is also called a Ladder or Bolthole tape.

Industrial grade tape has a lower bulk than Premium grade (the same size tape weighs more in Premium grade than Industrial grade as it has more fiberglass content). Available with and without Pressure Sensitive Adhesive (PSA).

1500°F / 815°C continuous rating, high insulation value & excellent personnel protection

Very High Temperature Heat Resistant Vermiculite Coated Fiberglass Tape Industrial Grade

Part Number	Width in / mm		Price per Roll By Thickness: A / B	
			"A"	"B"
			no PSA / with PSA	no PSA / with PSA
AB-VTI-M013-08-X-Z	.5	13	\$ 366.57* / \$ 482.90 *NOTE	
AB-VTI-M019-12-X-Z	.75	19	\$ 62.53 / \$ 110.70	\$ 164.93 / \$ 244.61
AB-VTI-M025-16-X-Z	1.0	25	\$ 66.84 / \$ 117.13	\$ 87.37 / \$ 139.00
AB-VTI-M032-20-X-Z	1.25	32	\$ 73.60 / \$ 132.90	\$ 94.67 / \$ 150.63
AB-VTI-M038-24-X-Z	1.5	38	\$ 75.06 / \$ 135.07	\$ 96.90 / \$ 156.90
AB-VTI-M051-32-X-Z	2.0	51	\$ 81.40 / \$ 148.20	\$ 104.03 / \$ 170.83
AB-VTI-M064-40-X-Z	2.5	64	\$ 101.43 / \$ 176.43	\$ 124.90 / \$ 198.79
AB-VTI-M076-48-X-Z	3.0	76	\$ 108.50 / \$ 190.07	\$ 126.23 / \$ 207.81
AB-VTI-M089-56-X-Z	3.5	89	\$ 114.96 / \$ 198.27	\$ 136.23 / \$ 219.53
AB-VTI-M102-64-X-Z	4.0	102	\$ 122.71 / \$ 215.87	\$ 146.17 / \$ 239.33
AB-VTI-M127-80-X-Z	5.0	127	\$ 145.13 / \$ 258.07	\$ 164.80 / \$ 294.47
AB-VTI-M152-96-X-Z	6.0	152	\$ 150.27 / \$ 281.80	\$ 185.37 / \$ 316.70

- For the "X" value, specify A or B in part number to correspond to the desired thickness.
A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm
- For "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape
- * **NOTE: 0.5" wide x 1/16" tape roll is 500 feet in length.**

Example: AB-VTI-B-24-P-PSA is a .125" thick tape, 1.5" wide, Plain style, with PSA coating.