

High Temperature, Heat & Chemical Resistant Fiberglass Braided Sleeve with PTFE (Teflon®) Coating



- Available in 1/16" & 1/8" wall thickness
- PTFE (Teflon®) Impregnation

This sleeve offers the advantage of a non-
asbestos material with higher temperature range
and with excellent resistance to almost all
solvents, caustics and acids.

The base fabric is rated to 1000°F / 537°C.

PTFE melting point is 620°F / 327°C.

550°F / 287°C continuous rating, high insulation value & excellent personnel protection

| High-Temperature, Heat & Chemical Resistance Braided Fiberglass Sleeve with PTFE (Teflon®) Coating | | | | | | |
|--|--------------------------|-----|-----|--|-----------------------------------|------------------------------------|
| Part Number | Size in / mm / -dash# | | | Feet per Spool Thin Wall / Thick Wall | Price / foot Thin wall PTFE | Price / foot Thick wall PTFE |
| | | | | | | |
| AB-PTS-M006-04-X | .250 | 6 | -04 | 1400 / 700 | \$ 1.68 | \$ 3.28 |
| AB-PTS-M010-06-X | .375 | 10 | -06 | 1400 / 600 | \$ 1.88 | \$ 3.64 |
| AB-PTS-M013-08-X | .500 | 13 | -08 | 1000 / 330 | \$ 2.44 | \$ 6.16 |
| AB-PTS-M016-10-X | .625 | 16 | -10 | 900 / 315 | \$ 3.28 | \$ 6.60 |
| AB-PTS-M019-12-X | .750 | 19 | -12 | 750 / 300 | \$ 3.88 | \$ 6.64 |
| AB-PTS-M022-14-X | .875 | 22 | -14 | 650 / 300 | \$ 4.40 | \$ 6.72 |
| AB-PTS-M025-16-X | 1.000 | 25 | -16 | 500 / 290 | \$ 5.32 | \$ 7.28 |
| AB-PTS-M032-20-X | 1.250 | 32 | -20 | 450 / 280 | \$ 6.24 | \$ 7.92 |
| AB-PTS-M038-24-X | 1.500 | 38 | -24 | 350 / 225 | \$ 7.68 | \$ 9.36 |
| AB-PTS-M041-26-X | 1.625 | 41 | -26 | 300 / 208 | \$ 7.72 | \$ 9.43 |
| AB-PTS-M044-28-X | 1.750 | 44 | -28 | 300 / 208 | \$ 8.12 | \$ 9.92 |
| AB-PTS-M051-32-X | 2.000 | 51 | -32 | 250 / 190 | \$ 9.98 | \$ 13.40 |
| AB-PTS-M057-36-X | 2.250 | 57 | -36 | 250 / 190 | \$ 10.31 | \$ 14.11 |
| AB-PTS-M064-40-X | 2.500 | 64 | -40 | 225 / 180 | \$ 11.88 | \$ 14.52 |
| AB-PTS-M070-44-X | 2.750 | 70 | -44 | 225 / 180 | \$ 12.03 | \$ 15.48 |
| AB-PTS-M076-48-X | 3.000 | 76 | -48 | 200 / 175 | \$ 13.12 | \$ 18.16 |
| AB-PTS-M083-52-X | 3.250 | 83 | -52 | 200 / 175 | \$ 13.43 | \$ 18.58 |
| AB-PTS-M089-56-X | 3.500 | 89 | -56 | 190 / 170 | \$ 14.24 | \$ 19.56 |
| AB-PTS-M095-60-X | 3.750 | 95 | -60 | 190 / 170 | \$ 15.09 | \$ 20.16 |
| AB-PTS-M102-64-X | 4.000 | 102 | -64 | 175 / 140 | \$ 17.28 | \$ 22.12 |
| AB-PTS-M114-72-X | 4.500 | 114 | -72 | 175 / 140 | \$ 20.66 | \$ 29.23 |
| AB-PTS-M127-80-X | 5.000 | 127 | -80 | 120 / 100 | \$ 24.76 | \$ 37.68 |

For the "X" value, use "N" to specify Thin Wall; use "W" to specify Thick Wall

Thin Wall = 1/16" / 1.59mm • Thick Wall = 1/8" / 3.18mm

This Product is Available By-The-Foot