

High Temperature Heat & Chemical Resistance Fiberglass Tape with PTFE (Teflon®) Coating: Premium Grade



- Available in three thicknesses
- PTFE (Teflon®) Impregnation

This tape offers the advantage of a non-asbestos material with higher temperature range and with excellent resistance to almost all solvents, caustics and acids.

The base fabric is rated to 1000°F / 537°C.

PTFE melting point is 620°F / 327°C.

Offered in Plain and Drop Warp.

550°F / 287°C continuous rating, high insulation value & excellent personnel protection

High Temperature, Heat & Chemical Resistance Fiberglass Tape with PTFE (Teflon) Coating: Premium Tape					
Part Number	Width in / mm		Price per Roll By Thickness: A / B / C		
			"A"	"B"	"C"
			.0625"/1.59mm	.125"/3.18mm	.250"/6.35mm
AB-PTTP-M013-08-X-Z**	.5	13	\$ 61.13	\$ 94.93	NA
AB-PTTP-M019-12-X-Z**	.75	19	\$ 65.27	\$ 105.33	\$ 199.93
AB-PTTP-M025-16-X-Z	1.0	25	\$ 105.27	\$ 165.80	\$ 305.63
AB-PTTP-M032-20-X-Z	1.25	32	\$ 148.40	\$ 229.83	\$ 405.33
AB-PTTP-M038-24-X-Z	1.5	38	\$ 191.53	\$ 293.70	\$ 505.03
AB-PTTP-M051-32-X-Z	2.0	51	\$ 241.93	\$ 372.20	\$ 634.07
AB-PTTP-M064-40-X-Z	2.5	64	\$ 292.33	\$ 452.80	\$ 736.73
AB-PTTP-M076-48-X-Z	3.0	76	\$ 342.60	\$ 532.33	\$ 900.27
AB-PTTP-M089-56-X-Z	3.5	89	\$ 392.93	\$ 611.73	\$ 1041.37*
AB-PTTP-M102-64-X-Z	4.0	102	\$ 443.13	\$ 691.07	\$ 1179.93
AB-PTTP-M127-80-X-Z	5.0	127	\$ 557.27	\$ 863.53	\$ 1458.53*
AB-PTTP-M152-96-X-Z	6.0	152	\$ 658.27	\$ 1035.67	\$ 1776.60

- For the "X" value, specify "A", "B" or "C" in the part number to correspond to the desired thickness
A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm C = 1/4" / .250" / 6.35mm
- For "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape

Example: AB-PTTP-B-24-P is a .125" thick tape, 1.5" wide, Plain style

- All tapes are 100 foot lengths.
- Items with * may have higher minimum order quantities – please call.
- ** .5"/13mm and .75"/19mm width tapes are not available in Drop Warp

High Temperature Heat & Chemical Resistance Fiberglass Tape with PTFE (Teflon®) Coating: Industrial Grade



- Available in three thicknesses
- PTFE (Teflon®) Impregnation

This tape offers the advantage of a non-asbestos material with higher temperature range and with excellent resistance to almost all solvents, caustics and acids.

The base fabric is rated to 1000°F / 537°C.

PTFE melting point is 620°F / 327°C.

Offered in Plain and Drop Warp.

550°F / 287°C continuous rating, high insulation value & excellent personnel protection

High Temperature, Heat & Chemical Resistance Fiberglass Tape with PTFE (Teflon) Coating: Industrial Tape				
Part Number	Width in / mm		Price per Roll By Thickness: A / B	
			"A" .0625"/1.59mm	"B" .125"/3.18mm
AB-PTTI-M013-08-X-Z**	.5	13	\$ 216.33	\$ 56.57
AB-PTTI-M019-12-X-Z**	.75	19	\$ 47.97	\$ 68.13
AB-PTTI-M025-16-X-Z	1.0	25	\$ 79.93	\$ 117.90
AB-PTTI-M032-20-X-Z	1.25	32	\$ 110.00	\$ 162.53
AB-PTTI-M038-24-X-Z	1.5	38	\$ 140.10	\$ 207.17
AB-PTTI-M051-32-X-Z	2.0	51	\$ 176.97	\$ 260.57
AB-PTTI-M064-40-X-Z	2.5	64	\$ 212.70	\$ 315.20
AB-PTTI-M076-48-X-Z	3.0	76	\$ 249.83	\$ 370.27
AB-PTTI-M089-56-X-Z	3.5	89	\$ 286.67	\$ 420.93
AB-PTTI-M102-64-X-Z	4.0	102	\$ 323.50	\$ 471.60
AB-PTTI-M127-80-X-Z	5.0	127	\$ 387.03	\$ 581.10
AB-PTTI-M152-96-X-Z	6.0	152	\$ 467.23	\$ 699.20

- For the "X" value specify "A" or "B" in the part number to correspond to the desired thickness
A = 1/16" / .0625" / 1.59mm B = 1/8" / .125" / 3.18mm
- For "Z" value in part number: use "-P" for Plain style tape or "-DW" for Drop Warp style tape

Example: AB-PTTI-B-24-P is a .125" thick tape, 1.5" wide, Plain style

- All tapes are 100 foot lengths.
- Items with * may have higher minimum order quantities – please call.
- ** .5"/13mm and .75"/19mm width tapes are not available in Drop Warp