

High Temperature Heat & Chemical Resistance Square Braided Fiberglass Rope with PTFE (Teflon) Coating



- PTFE (Teflon®) Impregnation

This rope offers the advantage of a non-asbestos material with higher temperature range and with excellent resistance to almost all solvents, caustics and acids.

The base fabric is rated to 1000°F / 537°C.

PTFE melting point is 620°F / 327°C.

550°F / 287°C continuous rating, high insulation value & excellent personnel protection

| High Temperature & Chemical Resistance Fiberglass Square Braided Rope with PTFE (Teflon®) Coating | | | |
|---|----------------------|----------------|----------------|
| Part Number | OD Size inch / mm | Price per foot | Feet per Spool |
| AB-PTSFR-M006-04 | 0.250 / 6 | \$ 5.60 | 375 |
| AB-PTSFR-M008-05 | 0.312 / 8 | \$ 4.90 | 315 |
| AB-PTSFR-M010-06 | 0.375 / 10 | \$ 5.07 | 285 |
| AB-PTSFR-M011-07 | 0.437 / 11 | \$ 6.80 | 212 |
| AB-PTSFR-M013-08 | 0.500 / 13 | \$ 8.90 | 162 |
| AB-PTSFR-M014-09 | 0.562 / 14 | \$ 11.33 | 127 |
| AB-PTSFR-M016-10 | 0.625 / 16 | \$ 13.70 | 105 |
| AB-PTSFR-M019-12 | 0.750 / 19 | \$ 19.20 | 75 |
| AB-PTSFR-M022-14 | 0.875 / 22 | \$ 26.17 | 55 |
| AB-PTSFR-M025-16 | 1.000 / 25 | \$ 31.98 | 45 |
| AB-PTSFR-M032-20* | 1.250 / 32 | \$ 46.17 | 26 |
| AB-PTSFR-M038-24* | 1.500 / 38 | \$ 66.60 | 18 |
| AB-PTSFR-M051-32* | 2.000 / 51 | \$ 109.10 | 11 |