

ScuffSleeve™ Abrasion Protection Sleeve: for Hose, Wire and Cable



- Abrasion resistance sleeve for hoses, wires and cables.
- Exceeds the new "Line of Sight" operator protection regulations EN982 ISO norm 833 EN414 for hose blowout.
- Ultra tight weave provides leak containment.
- Tight weave and smooth surface resists abrasive wear.
- Less bulky than older cordura sleeves.
- Nylon 6: excellent UV protection.
- MSHA approved.
- Exceeds ISO 6945 abrasion standard and ISO 8031 conductivity standard.
- Easily cut to length or cut with heat knife.
- Useable -60°F to +375°F.
- Also available as a Sleeve with Velcro for easy retrofit.

Standard length is 150 feet per coil.

Helps to organize and bundle hoses and cables, while proving heat resistance to a maximum of 375°F continuous duty, and provides excellent abrasion, scuff and wear resistance.

ScuffSleeve™ Nylon Abrasion Protection Sleeve				
Part Number	ID Size			Price per Foot
	inch	mm	-dash	
AB-APS-M017-11	0.67	17	-11	\$ 1.52
AB-APS-M020-13	0.79	20	-13	\$ 1.57
AB-APS-M023-15	0.91	23	-15	\$ 1.62
AB-APS-M024-16	0.96	24	-16	\$ 1.79
AB-APS-M026-17	1.06	26	-17	\$ 1.88
AB-APS-M030-20	1.22	30	-20	\$ 1.97
AB-APS-M036-23	1.42	36	-23	\$ 2.13
AB-APS-M039-26	1.57	39	-26	\$ 2.28
AB-APS-M043-28	1.73	43	-28	\$ 2.43
AB-APS-M047-30	1.85	47	-30	\$ 2.74
AB-APS-M055-35	2.17	55	-35	\$ 3.16
AB-APS-M059-38	2.36	59	-38	\$ 3.43
AB-APS-M072-46	2.87	72	-46	\$ 4.67
AB-APS-M074-48	2.95	74	-48	\$ 5.67
AB-APS-M092-59	3.66	92	-59	\$ 5.80
AB-APS-M125-80	4.94	125	-80	\$ 9.77

* minimum order is full coil/spool length

ScuffSleeve™ VC Abrasion Protection Sleeve, with Velcro: for Wire, Cable and Hose



- Abrasion resistance for hoses and cables.
- Sleeve with Velcro for easy retrofit.

This abrasion protection sleeve is manufactured from highly dense and tough Nylon, available as a sleeve or a sleeve with velcro fastener. We only use genuine velcro to ensure high holding strength of the fastener

Available in standard sizes and larger or custom sizes can be easily fabricated if required.

Helps to organize and bundle hoses and cables, while proving heat resistance to a maximum of 375°F continuous duty, and provides excellent abrasion, scuff and wear resistance.

ScuffSleeve™ VC: Nylon Abrasion Protection Sleeve with Velcro				
Part Number	Size			Price per Foot
	inch	mm	-dash	
AB-APS-VC -16	1.000	25	-16	\$ 7.49
AB-APS-VC -20	1.250	32	-20	\$ 8.66
AB-APS-VC -24	1.500	38	-24	\$ 9.25
AB-APS-VC -28	1.750	44	-28	\$ 9.80
AB-APS-VC -32	2.000	51	-32	\$ 10.25
AB-APS-VC -40	2.500	64	-40	\$ 11.55
AB-APS-VC -48	3.000	76	-48	\$ 12.65
AB-APS-VC -56	3.500	89	-56	\$ 13.25
AB-APS-VC -64	4.000	102	-64	\$ 13.97
AB-APS-VC -72	4.500	114	-72	\$ 15.45
AB-APS-VC -80	5.000	127	-80	\$ 16.87
AB-APS-VC -88	5.500	140	-88	\$ 17.43
AB-APS-VC -96	6.000	152	-96	\$ 17.51
AB-APS-VC -104	6.500	165	-104	\$ 19.21